



TufBond MP

Multipurpose Epoxy Primer for Floor & Wall Coatings

Uses

TufBond MP is a modified solvent based epoxy primer designed to provide a smooth, damp free substrate for floor coatings which gives better adhesion to new and existing concrete.

- Car park decks
- Car park ramps
- Aircraft hangars
- Transport depots
- Service centers, garages
- Workshops
- Primer for wall coatings

Typical Applications & Advantages

- Apply to dry or damp surface.
- Suitable for all zones in a car park
- Seamless and water tight
- Resistant to chemical attack
- Supplied in pre weighed unit

Product Description

TufBond MP is a modified two component solvent based epoxy primer designed to provide a smooth, damp free substrate for epoxy floor coatings which gives better adhesion to new and existing concrete. It is supplied as factory pre-weighed units as Part A & Part B.

Typical Properties

Specific gravity	: 0.99 @25±2°C
Full cure	: 7 days @ 25±2°C

Technical Support

GIC provides a comprehensive technical support service to specifiers, end users and contractors and is able to offer on-site technical assistance.

Instructions for Use

Surface Preparation: Ensure the concrete foundation surface is dimensionally stable and free of dirt, dust, oil, laitance, paint, curing compounds etc. Bolt holes and fixing pockets should be free from any dirt or debris. If possible a roughened surface is preferable to smooth surfaces. Metal surfaces must be free from rust, loose scaling and paint. Shuttering should be

covered with polyethylene to ensure a clean release.

Mixing: Do not commence mixing until all surface preparation, cleaning and shuttering is complete. Add Part B to Part A in a suitable forced action mixer; alternatively use a slow speed drill and paddle. Continue mixing until a completely homogenous material is obtained.

Application: Apply **TufBond MP** to the prepared surface at an application rate in the range of 0.1 to 0.2 ltr/m². Quantity will depend on surface texture and porosity. Apply by brush or roller across the whole surface ensuring uniformity of thickness. Allow **TufBond MP** to dry completely before applying top coat.

Packaging & Storage

TufBond MP is supplied in 9 litre pack and it has a minimum shelf life of 12 months provided it is stored under cover, out of direct sunlight.

Coverage

Coverage varies depending on ambient conditions, porosity of the surface, application method, etc. Typically coverage of 0.1 to 0.2 ltr/m² /coat is possible.

Equipment Care

Clean all equipment promptly using GIC Solvent No.1. Cured material will have to be mechanically removed.

Health & Safety Precautions

TufBond MP does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately – do not induce vomiting.

For further information refer to the Material Safety Data Sheet available for this product.





Important note

GIC endeavors to ensure that the technical information contained herein is true, accurate and represents our best knowledge and experience. No warranty is given or implied, as GIC has no control over the conditions of use and the competence of any labor involved in the application are beyond our control.

As all GIC technical data sheets are updated on a regular basis it is the customer's responsibility to check that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended.

Rev: October 2007



Gulf International Chemicals SAOG

FACTORY & H.O.

P.O.BOX 132,

PC 124, Rusayl

Sultanate of Oman

Tel: +968 24446800

Fax: +968 24446808

Email:

gulfint@omantel.net.om

Gulf International Chemicals

REGIONAL OFFICE

P.O BOX: 98175,

DUBAI,

UAE

Tel: +971 4 2583221

Fax: +971 4 2583220

Email:

gic_dxb@emirates.net.ae

GIC



AN ISO 9001:2000 CERTIFIED COMPANY

www.gicomman.com