



GIC Bitumen Rubber Sealant

Thixotropic, Non-Slump Rubberized Bitumen Sealant.

Uses

- Used for the cold bonding of roofing felt.
- Used in roofing where sealing and pointing horizontal chases for waterproofing materials, flashing and guttering, etc. is required.

Typical Applications & Advantages

- Provides an impervious, flexible, malleable seal with excellent slump resistance.
- Excellent slump resistance.
- Versatile and economical.
- Maximum adhesion with high degree of flexibility.

Standards Compliance

GIC Bitumen Rubber Sealant complies with the requirements of the following standards:
ASTM D 1475
ASTM C 1250:93

Product Description

GIC Bitumen Rubber Sealant is a unique type of trowel applied sealant and adhesive. Due to the nature of the product, it may also be used for the cold bonding of roofing felt.

Typical Properties

Form	: Semi-stiff paste
Specific Gravity	: 1.2 - 1.3
Solids Content	: 80% min.

Technical Support

GIC provides a comprehensive technical support service to specifiers, end users and contractors and is able to offer on-site technical assistance.

Instructions for Use

Surface Preparation: All surfaces should be clean, dry and free from all dirt, dust and loosely adhering materials. Remove all oil and grease contamination.

Priming: Porous surfaces such as concrete, stone, brickwork, asphalt and timber should be

primed with GIC TufGuard BBP. Allow primer to become touch dry prior to sealant application.

Application: This may be applied by trowel, spatula or three-knot roofing brush. In vertical joints, apply sealant from the bottom upwards ensuring the entire volume of the joint is filled. Compress the sealant into the joint to give complete contact with joint surfaces. The use of a little cleaning solvent will help facilitate the smoothing process. Any masking tape used to protect adjacent surfaces should be removed immediately after tooling.

Cleaning: Clean tools and equipment after use with white spirit or similar solvent cleaner

Packaging & Storage

GIC Bitumen Rubber Sealant is available in 18kgs and it has a minimum shelf life of 12 months provided it is stored under cover, out of direct sunlight.

Health & Safety Precautions

GIC Bitumen Rubber Sealant does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If swallowed seek medical attention immediately – do not induce vomiting.

For further information refer to the Material Safety Data Sheet available for this product.

Important note

GIC endeavors to ensure that the technical information contained herein is true, accurate and represents our best knowledge and experience. No warranty is given or implied, as GIC has no control over the conditions of use and the competence of any labor involved in the application are beyond our control.





TufBond

As all GIC technical data sheets are updated on a regular basis it is the customer's responsibility to check that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended.

Rev: October 2007



**Gulf International
Chemicals SAOG**

FACTORY & H.O.
P.O.BOX 132,
PC 124, Rusayl
Sultanate of Oman

Tel: +968 24446800

Fax: +968 24446808

Email:
gulfint@omantel.net.om

**Gulf International
Chemicals**

REGIONAL OFFICE
P.O BOX: 98175,
DUBAI,
UAE

Tel: +971 4 2583221

Fax: +971 4 2583220

Email:
gic_dxb@emirates.net.ae



AN ISO 9001:2000 CERTIFIED COMPANY

www.gicomman.com