



GIC Release Agent

Oil Based Release Agent

Uses

- For quick, clean and easy stripping of moulds and formwork.
- For high quality, fair-faced and stain-free concrete.

Typical Applications & Advantages

- Ensure easy release, reducing damage and improving efficiency of production.
- Minimizes surface blemishes and staining, promoting high quality fair-faced concrete even with white cement.
- Reduces opportunity of damage to formwork, extending usable life.
- Minimizes cleaning of formwork before re-use.
- Suitable for use with virtually all types of formwork.
- Inhibits corrosion of steel formwork.

Product Description

GIC Release Agent is a specially formulated blend of mineral oils with a chemically active release agent that is suitable for application to mould and shutter faces prior to casting concrete in order to obtain a clean release. The alkali reactive chemicals promote a water-repellent interface which protects both steel and timber formwork whilst ensuring the resultant concrete has a smooth, hard, uniform finish with reduced incidence of blowholes.

GIC Release Agent will also allow air to escape from the interface during placing and vibration thereby resulting in a reduction of remedial costs. Use of **GIC Release Agent** has no negative effect on the quality of the concrete nor will it impair the adhesion of subsequent coatings providing application is made at recommended coverage rates.

When applied at recommended coverage rates **GIC Release Agent** is non toxic and may be used in for concrete in potable water applications.

Typical Properties

Color	:	Pale straw liquid
Specific Gravity	:	0.83 @ ±2°C
Coverage Rate	:	30 - 60 m ² /litre/coat

Technical Support

GIC provides a comprehensive technical support service to specifiers, end users and contractors and is able to offer on-site technical assistance.

Instructions for Use

Preparation: New moulds, if extensive reuse is anticipated, treat new moulds with a polyurethane coating. For used moulds, remove all traces of adherent material i.e. concrete, oil etc. The use of an acid etch will assist in the cleaning process.

Application: **GIC Release Agent** may be applied by brush, roller or lightweight spray. Apply in an even, continuous film avoiding excessive application. If, after the first application **GIC Release Agent** is absorbed into the shutter a further application should be made. Apply **GIC Release Agent** before the first casting and thereafter between castings.

Coverage

Depending on the porosity and texture of the mould surface, typical coverage rates of 30 to 60 m²/litre/coat may be obtained.

Packaging & Storage

GIC Release Agent is available in 20 litre and 210 litre drums and it has a minimum shelf life of 12 months provided it is stored under cover, out of direct sunlight.

Health & Safety Precautions

GIC Release Agent does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come into contact with skin and eyes. Suitable protective gloves and goggles should be worn. Splashes on the skin should be removed with water. In case of contact with eyes rinse immediately with plenty of water and seek medical advice. If





swallowed seek medical attention immediately – do not induce vomiting.

For further information refer to the Material Safety Data Sheet available for this product.

Important note

GIC endeavors to ensure that the technical information contained herein is true, accurate and represents our best knowledge and experience. No warranty is given or implied, as GIC has no control over the conditions of use and the competence of any labour involved in the application are beyond our control.

As all GIC technical data sheets are updated on a regular basis it is the customer's responsibility to check that the product is suitable for the intended application, and that the actual conditions of use are in accordance with those recommended.

Rev: October 2007

Gulf International Chemicals SAOG

FACTORY & H.O.

P.O.BOX 132,

PC 124, Rusayl

Sultanate of Oman

Tel: +968 24446800

Fax: +968 24446808

Email:
gulfint@omantel.net.om

Gulf International Chemicals

REGIONAL OFFICE

P.O BOX: 98175,

DUBAI,

UAE

Tel: +971 4 2583221

Fax: +971 4 2583220

Email:
gic_dxb@emirates.net.ae

GIC



AN ISO 9001:2000 CERTIFIED COMPANY

www.gicomman.com